

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 1 May 2003		2. REPORT TYPE View Graphs		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Multi-Scale Strain Measurements of a Polymeric Material				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) C.T. Liu				5d. PROJECT NUMBER 2302	
				5e. TASK NUMBER 0378	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRSM 10 E. Saturn Blvd. Edwards AFB, CA 93524-7680				8. PERFORMING ORGANIZATION REPORT NUMBER AFRL-PR-ED-VG-2003-117	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S NUMBER(S) AFRL-PR-ED-VG-2003-117	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
<h1>20030618 115</h1>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE	A		Sheila Benner
Unclassified	Unclassified	Unclassified			19b. TELEPHONE NUMBER (include area code) (661) 275-5693

FILE

MEMORANDUM FOR PRS (In-House Publication)

FROM: PROI (STINFO)

01 May 2003


SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-VG-2003-117**
C.T. Liu (AFRL/PRSM) et al., "Multi-Scale Strain Measurements of a Polymeric Material"

5642

2003 SEM Conf: Exprmtl & Appl Mechanics
(Charlotte, NC, 2-4 June 2003) (Deadline: 25 May 2003)


(Statement A)

Multi-Scale Strain Measurements of a Polymeric Material




C. T. Liu
AFRL/PRSM
10 E. Saturn Blvd.
Edwards AFB CA 93524-7680, U.S.A

Fu-Pen Chiang
Department of Mechanical Engineering
State University of New York
Stony Brook NY 11790





Objectives




- Determine the Displacement and Strain Fields in a Polymeric Material
- Investigate the Local Damage Mechanisms and Failure Behavior near the Crack Tip




Testing Set-Up








Strain Distributions (2.5mm x 2.0mm)




ϵ_{yy} field, Load = 52 grams




ϵ_{xx} field, Load = 52 grams




Strain Distributions (1.2mm x 1.0mm)





ϵ_{yy} field, Load = 41 grams




ϵ_{xx} field, Load = 41 grams




Strain Distributions (0.5mm x 0.45mm)





ϵ_{yy} field, Load = 47 grams




ϵ_{xx} field, Load = 47 grams



Strain Distributions (0.065mm x 0.055mm)






ϵ_{yy} field, Load = 49 grams




ϵ_{xx} field, Load = 49 grams


Strain Distribution (0.065mm x 0.055mm)




ϵ_{yy} field (3-D), Load = 49 grams




ϵ_{xx} field (3-D), Load = 49 grams




Strain Ratio ($-\epsilon_{xx}/\epsilon_{yy}$) Distributions at Different Magnifications




40x "Poisson Ratio" distribution




80x







Strain Ratio ($-\varepsilon_{xx}/\varepsilon_{yy}$) Distributions at Different Magnifications




200x





1500x








Side View of Crack Tip at 150x & 400x







Side View of Crack Tip at 500x & 1000x






Crack Tip Top View





07/12/2002


150x


200um




Standard Deviation / Mean of ϵ_{xx} Vs. Examined Area







Conclusions



- The strain distributions vary with the size of the area, A , in which the data were analyzed.
- When the size of A is smaller or equal to $1.5 \text{ mm} \times 1.5 \text{ mm}$, the nonuniformity of the strain distributions is increased. Especially, when the size of A is equal to $0.065 \text{ mm} \times 0.055 \text{ mm}$, both tensile and compressive strain fields exist in the small area
- The representative area, which is defined as an area in which the material's microstructure has no significant effect on the strain distribution, of the material considered is $1.5 \text{ mm} \times 1.5 \text{ mm}$.
- A highly damaged region of 20-50 micron long is developed at the crack tip.
- The crack growth mechanism involves voids formation ahead of the crack tip and the coalescence of the main crack tip with the void.